

Product Name : Highbay lights :

Red Band:

Features:

1. Efficient thermal exchange
2. Special silicone gasket
3. Energy savings up to 90%
4. Customizable
5. Smart lighting
6. High performance SMD design

Mounting options:

1. Hook mounting
2. Chain mounting
3. Rotatable bracket

Dimensions:

1. 100w
2. 150w
3. 200w

LED High Bay Light Specifications

Model Number	GA20-HBA01-100W	GA20-HBA02-150W	GA20-HBA03-200W
Wattage	100 W	150 W	200 W
Luminous Flux	13000 LM	19500 LM	26000 LM
Efficacy	130 LM/W	130 LM/W	130 LM/W
LED Driver	Meanwell	Meanwell	Meanwell
LED Chip	Philips	Philips	Philips
CCT	3000K, 4000K, 5000K	3000K, 4000K, 5000K	3000K, 4000K, 5000K
Ingress Protection (IP)	IP65	IP65	IP65
Input Voltage	100 - 240 VAC / 100 - 227 VAC, 50-60 Hz, PF 0.95	100 - 240 VAC / 100 - 227 VAC, 50-60 Hz, PF 0.95	100 - 240 VAC / 100 - 227 VAC, 50-60 Hz, PF 0.95
Operating Temperature	-30°C to +50°C	-30°C to +50°C	-30°C to +50°C

Lifetime of LED @Ta=25°C	50000 Hrs.	50000 Hrs.	50000 Hrs.
Net Weight	3.5 kg	4.6 kg	5.1 kg